

OAK LEAF

HD PLUS

OAKLEAF HD PLUS LAMINATE CLICK FLOORING FOR FLOATING INSTALL

OAKLEAF HD PLUS laminate flooring delivers amazing realism with décor visuals so natural you would think you were looking at a real natural timber plank. Using the latest digital imaging technology, a stunning range has been created that showcases popular Australian Timber species along with Oak & Hickory décors. Featuring a moisture protected treatment for the micro bevel edges along with an amazing 30 pattern repeats, these planks deliver all the natural charm & character you would expect from a natural timber floor. OAKLEAF HD PLUS also features a 48hr independently tested Water-Resistant core providing ultimate peace of mind for when little accidents occur.

OAKLEAF HD PLUS laminate is AC4 rated, making it tough enough for everyday living and ideally suited for the wear and tear associated with modern family environments. OAKLEAF HD PLUS laminate is dimensionally stable, exceptionally durable and offers great visual appeal for residential décors, and commercial fit-out.

OAKLEAF HD PLUS CLICK FLOORING 2200 x 196 x 12mm AC4						48hr WATER RESISTANT
Colour	Scotia	Trim	Sqm/Ctn	Planks/Ctn	Ctns/Pallet	Micro Bevel
Alpine Mist	Ghost Gum	Lugarno	1.725	4	60	Yes 4 sides
Arctic Fox	Limesmoke	Moon	1.725	4	60	Yes 4 sides
Bedrock	Leysin	Sunshine	1.725	4	60	Yes 4 sides
Blackbutt	Blackbutt	Blackbutt	1.725	4	60	Yes 4 sides
Brush Box	Brush Box	Kempas	1.725	4	60	Yes 4 sides
Clove	Rift	Moon	1.725	4	60	Yes 4 sides
Delta Sand	Limesmoke	Lugarno	1.725	4	60	Yes 4 sides
Hickory	Brazilian Oak	Zermatt	1.725	4	60	Yes 4 sides
Ironbark	Brush Box	Kempas	1.725	4	60	Yes 4 sides
Natural	Wheat	Zermatt	1.725	4	60	Yes 4 sides
Sierra Oak	Wheat	Sunshine	1.725	4	60	Yes 4 sides
Silk Grey	Seashell	Moon	1.725	4	60	Yes 4 sides
Spotted Gum	Spotted Gum	Spotted Gum	1.725	4	60	Yes 4 sides
Wolf Grey	Lugarno	Moon	1.725	4	60	Yes 4 sides

Key Features: Interior 48hr Water Resistant warranty incorporating a 3-step process that includes a T Seam tight lock click profile, moisture protection treated bevel edges & independently tested water-resistant core. High Definition digital imaging for dynamic realism. Imaging based on natural timber samples with a 30 pattern repeat production process. Project size & installation blending will determine extent of variation.

Classic Width: 196mm planks for Oak, Hickory & Australian Timber décors. 1.725m²/Ctn.

Description & Profile: 48hr Water-resistant AC4 Laminate. Valinge Click profile. Moisture protection treated Micro Bevel V4.

Surface features: High Definition Digital Print realistic timber visuals, colours, and textures. Super Matte coating.

Swell Testing: Conforms to EN 13329:2016 + A1:2017 & ISO 24336:2005 & NALFA, T Seam - Swell & Seepage Test >80hrs.

Slip Rating: AS 4586:2013 Appendix A, P3. **Fire Test:** CHF Value 4.4Kw/m². HF -30 Value 5.4Kw/m². **Smoke Value 12% min.**

VOC: GOLD Greenguard Certified for Low Chemical Emissions UL.COM/GG UL 2818-2013, 108959-420, 09-2018-09-2021

© Preference Floors. Head Office 02 97381188.

"The preferred choice"

Homemirus Pty Ltd trading as


Preference
 FLOORS